

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 225 967 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

18.06.2003 Bulletin 2003/25

(21) Application number: 00968198.2

(22) Date of filing: 06.10.2000

(51) Int Cl.7: B01D 53/60, B01D 53/14

(86) International application number:
PCT/IL00/00632

(87) International publication number:
WO 01/026784 (19.04.2001 Gazette 2001/16)

(54) A METHOD FOR REMOVING ACIDIC GASES FROM WASTE GAS

EIN VERFAHREN ZUR ENTFERNUNG VON SAUREN GASEN AUS ABGASEN

PROCEDE D'ELIMINATION DE GAZ ACIDES A PARTIR DE GAZ RESIDUAIRES

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

(30) Priority: 12.10.1999 IL 13234799

(43) Date of publication of application:
31.07.2002 Bulletin 2002/31

(73) Proprietor: LEXTRAN LTD.
12900 Katzrin (IL)

(72) Inventors:

- KHITRIK, Adolf
Katzrin 12900 (IL)
- PIPKO, Gregori
12900 Katzrin (IL)
- DORON, Benjamin
96146 Jerusalem (IL)

(74) Representative: Söllner, Udo et al
Reinhardt Söllner Ganahl
Patentanwälte
Postfach 1226
85542 Kirchheim bei München (DE)

(56) References cited:
US-A- 3 607 004 US-A- 3 784 478

- DATABASE WPI Section Ch, Week 197909
Derwent Publications Ltd., London, GB; Class
E36, AN 1979-17573B XP002155369 & SU 602 212
A (NIKITIN YU E), 15 March 1978 (1978-03-15)
- DATABASE WPI Section Ch, Week 197913
Derwent Publications Ltd., London, GB; Class
E36, AN 1979-25482B XP002155370 & SU 606 606
A (AS BASHKIR BR CHEM), 12 April 1978
(1978-04-12)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 225 967 B1

Description

FIELD OF THE INVENTION

5 [0001] The present invention relates to a method for removing acidic gases of sulfur and nitrogen oxides from waste gases. More specifically the present invention relates to a method for removing acid gases of SO_2 and NO_x , by contacting the waste gas with an emulsion of water in organic sulfoxides, in particular of water in oil-derived-sulfoxides in the presence of a stream of air or ozonated air. The organic sulfoxide phase can be regenerated after the emulsion is loaded with pollutants, by letting the emulsion to settle down and separate into two phases. The aqueous phase obtained after the separation contains sulfate and nitrate ions which can be collected and used as valuable chemicals.

BACKGROUND

15 [0002] Industrially developed countries generate billions of tons of air pollutants, a great part accounts to the combustion of coal, oil, and gasoline in electric power plants. Other major air pollution sources include petroleum refineries, cement plants and petrochemical plants.

Among the most troublesome air pollutants emitted into the atmosphere are acid gases and in particular SO_2 and NO_x . These gases are the major cause for acid rain, for smog and for human discomfort and disability.

20 Sulfur dioxide is released into the atmosphere from the combustion of sulfur containing compounds in fossil fuels, such as gas, petroleum, and coal. SO_2 is a heavy, colorless gas with a characteristic, suffocating odor. In moist air it is slowly oxidized to sulfuric acid and contributes to acid rain. NO_x gases, on the other hand, partly originate from the combustion of nitrogen containing compounds but mostly they originate from the reaction between elementary oxygen and nitrogen present in the air at the elevated temperatures at which various industrial processes (and combustion) take place. Therefore, the problem of NO_x is even more difficult to overcome as it is a problem inherent to these processes and its generation cannot be avoided. Nitrogen oxides, in addition to their contribution to acid rain, breaks down to form ozone and reacts with other atmospheric pollutants to form photochemical smog which irritates sensitive membranes and damages plants.

25 [0003] The increasing environmental awareness during the last decades has led in many countries to governmental regulations, enforcing standards for maximum air pollutants emission on power plants and industries, in order to achieve air quality standards for various hazard materials. For example, in the U.S., the Clean Air Act of 1967 as amended in 1970, 1977, and 1990 is the legal basis for air-pollution control throughout the U.S. The 1990 amendments to the Clean Air Act of 1967 put in place regulations to reduce the release of sulfur dioxide from power plants to 10 million tons per year by January 1, 2000. This amount is about one-half the emissions of 1990. In 1988, as part of the United Nations-sponsored Long-Range Transboundary Air Pollution Agreement, the United States, along with 24 other nations, ratified a protocol freezing the rate of nitrogen oxides emissions at 1987 levels.

30 [0004] The need to obey these regulations has led to the development of diversified methods for controlling and reducing the emission of air pollutants. In general, these methods include removing the hazardous material before it is used (for example, using low-content sulfur coal) or removing the pollutant after it is formed. For some air pollutants, (e.g., NO_x) only methods of the second class can be employed.

40 [0005] The present invention relates to methods of the second class.

[0006] Industrially emitted pollutant gases can be entrapped by liquids or solids traps that adsorb the harmful gases before they are released into the atmosphere. These traps are usually in the form of tower tanks contactors through which the waste gas is passed upward while the liquid, or a slurry, i.e. a mixture of liquids and solids, is descending downward. The agent which absorbs the pollutants and prevent their emitting into the atmosphere is called the scrubbing agent. When this agent is a liquid, it is sometimes the practice to fill the tower with inert particles in order to increase the contact surface between the scrubbing agent and the waste gas and to increase the residence time of the gas inside the reactor. In such cases it is also the practice to circulate the liquid scrubbing agent through the reactor until it is loaded with the pollutants.

45 [0007] Wet flue gas desulfurization, i.e., the removal of SO_2 processes typically involve the use of an alkaline cleansing liquid, such as a calcium-based slurry or a sodium-based or ammonia-based solution. These processes however are not suitable for the removal of nitrogen oxides. The currently used methods for the removal of NO_x from flue gas are mainly of the kind that is based on the reaction of NO and NO_2 with ammonia, with or without a catalyst, forming nitrogen and water. These methods are effective only within a narrow flue gas temperature range, are relatively high cost and involve the risk of ammonia leakage to the atmosphere. In the presence of catalyst the process is more efficient but its cost is even higher and the catalyst tends to be poisoned. In any case these methods require a special equipment useful only for the removal of NO_x .

55 [0008] US patent No. 3,6707,004 discloses a process for removing traces of hydrogen sulfide (H_2S) contained in gases. The process consists of passing the hydrogen sulfide-containing gas through a liquid phase consisting essen-

tially of iodine dissolved in an organic solvent US patent No. 3,784,478 teaches a process for removal of nitrogen oxides from the gaseous effluents of combustion processes utilizing gas-liquid absorption.

[0009] Russian patent No. 2099789 describes a process for removing sulphur dioxide from gasses by absorption with sulfoxides.

5 [0010] The processes described in US patent No. 3,6707,004, 3,784,478 and Russian patent No. 2099789 are disadvantageous since by these processes only one gas (NO_x or SO_2 or H_2O) can be removed from waste gases.

[0011] Therefore a great effort is put into developing new NO_x control methods which will remove simultaneously NO_2 and SO_2 from combustion flue gas. For example, US 4,418,044 teaches a scrubbing agent consisting of a solution of Fe(II) ions and thiosulfate in a miscible mixture of water and alcohol. US 4,885,146 teaches a similar scrubbing agent consisting of Fe(II) ions but in non-aqueous solvent (only up to 10% water). According to US 4,885,146 the scrubbing agent can be regenerated for reuse.

10 [0012] The cost of pollution reduction processes and equipment is, however, still very high and therefore intensive efforts are put into research in order to increase the efficiency of known processes and in order to find new more efficient and less energy consuming methods. These efforts concentrate on the following points: simplicity of process (i.e., involve low-cost equipment), the use of low-cost materials and the recycling of these materials, universality of process, i.e., removing as many pollutants as possible by the same process. Other, no less important, efforts are dedicated to finding processes in which the end products, not only are harmful, but can also be collected and be sold as useful materials (i.e., converting the harmful air pollutants into valuable materials) so that at least part of the investment will be earned back.

20 [0013] Therefore there is still a need for developing simple, more efficient and relatively low-cost, methods for air pollution control, especially methods which will clean fuel gases from both SO_2 and NO_x simultaneously in one process and with the same equipment.

[0014] It is the aim of the present invention to provide a method for removing acid gases of SO_2 and NO_x , simultaneously.

25 [0015] Yet it is another aim of the present invention to provide such a method which involves low-cost materials and equipment.

[0016] It is yet another aim of the present invention to provide such a method in which the scrubbing material is regenerated easily for further use.

30 [0017] It is another aim of the present invention to provide such a method which will also results in converting the SO_2 and NO_x into useful materials with commercial value.

SUMMARY OF THE INVENTION

35 [0018] The present invention relates to a method for removing acidic gases of SO_2 and NO_x from waste gases by contacting the waste gas with an emulsion of water-in- organic sulfoxides. The waste gas can be any waste gas containing said acidic gases, such as combustion flue gas and waste gases generated in various chemical processes. The organic sulfoxides are preferably oil-derived sulfoxides and in particular sulfoxides derived from diesel. The weight ratio of the water, organic sulfoxide in the emulsion is in the range 10:90 to 90: 10, preferably in the range 10:90 to 50:50.

40 [0019] The process of the present invention is carried out in an oxidation environment. Therefore if the waste gas mixture does not contain enough oxygen, an additional stream of air enriched with ozone (ozonated air) is added to the waste gas.

[0020] The scrubbing agent can be regenerated after it is loaded, by letting said scrubbing agent to separate into two phases, collecting the upper sulfoxide phase and adding to said sulfoxide phase a fresh amount of aqueous solution. The aqueous phase which is obtained after the separation of phases contains nitric and/or sulfuric acids and can be collected to be used as useful acid solutions or ammonium ions can be added acidic solution until neutralization occurs to obtain a solution of ammonium nitrate and/or ammonium sulfate salts useful as a fertilizer.

45 [0021] In another embodiment of the present invention the aqueous phase of the scrubbing agent is an aqueous solution of ammonium having pH equals or lower than 6 and after the separation of the emulsion the aqueous phase is a solution of ammonium nitrate and/or ammonium sulfate salts useful as a fertilizer. The source for the ammonium ions can be ammonia or ammonium carbonates (and bicarbonates) and ammonium carbamate..

50 [0022] According to the present invention, contacting the waste gas with the scrubbing agent can be conducted in a tower embedded with inert particles, wherein the waste gas is passed upward through the tower and the emulsion is circulated downward in a rate which ensures complete wetting of inert particles or can be conducted in a tower through which the waste gas is passed in an upward direction and the emulsion is sprayed into the tower from the upper opening of the tower forming a fog of said emulsion inside the tower.

DETAILED DESCRIPTION OF THE INVENTION

[0023] The main problem of entrapping acid gases in aqueous solutions is the instability of the intermediate species formed upon the dissolution of the acidic gases in water (e.g., HNO_2 , H_2SO_3), before they are oxidized into stable species. The instability results in the decomposition of the species and the releasing of the noxious gases from the solution. The present invention overcomes this problem by introducing an agent which binds the unstable species and forms a stable complex. Upon oxidation, a stable ion is formed and the complex decomposes, leaving the agent molecules free to bind to new dissolved pollutant molecules.

[0024] According to the present invention, this stabilizing agents are organic sulfoxides. Organic sulfoxides are known for their acid extraction properties. Of special interest are oil derived sulfoxides that are obtained by the oxidation of organic sulfides contained in oil. By oxidizing and extracting different fractions of oil, a mixture of sulfoxides is obtained, having molecular weight and boiling temperature according to the oil fraction from which they are derived. The diesel fraction (boiling temperature $190\text{--}360^\circ\text{C}$) is in particular a good source for oil-derived-sulfoxides, since this fraction is relatively rich in sulfur and the sulfoxide mixture so obtained is a liquid of low-cost.

[0025] Sulfoxides form a complex with the unstable dissolved acidic gases thus stabilizing these species and preventing their decomposition as explained in the following.


a. NO_x entrapping

[0026] The total concentration of NO_x produced in combustion processes is typically 200 - 1000 ppm, most of it in the form of nitric oxide (NO) and about 5% as nitrogen dioxide (NO_2).

[0027] NO is a relatively inert gas. It does not dissolve in water and forms no chemical compound with water or with alkalis, therefore it cannot be absorbed by basic aqueous solutions. In order for NO to be absorbed by aqueous solutions, it needs to be oxidized first by oxygen or by ozone:





or




[0028] When both NO and NO_2 present in the gas mixture they react to give:



[0029] The interaction of NO and NO_2 with water occurs according to the following possible reaction routes:




and




[0030] It is obvious from reactions (4-9) that in all cases, upon interaction of NO_2 (or NO and NO_2) with water, HNO_2 is formed and decomposed to give NO .

[0031] The present invention provides a way to avoid the decomposition of nitrous acid and the release of NO from the solution, by using organic sulfoxides, having the structure:



[0032] The free electron pair on the sulfur atom forms a bond with HNO_2 (J. Applied Chemistry, vol 4, 1986, 900-903):



[0033] Thus, the sulfoxide binds the HNO_2 and its decomposition is prevented. In the presence of oxidant, the bound nitrous acid is oxidized to nitric acid and loses its capability to bind to the sulfoxide. HNO_3 , whose water solubility is very high, moves into the aqueous phase and the sulfoxide molecules can adsorb another molecule of nitrous acid.


b. SO_2 entrapping

[0034] The combustion of coal, oil and other sulfur containing fuels produces a flue gas in which 98-99% of the sulfur is in the form of sulfur dioxide (SO_2) and 1-2% is sulfur trioxide (SO_3). For low and high sulfur coals the total concentration of SO_x is usually in the range of 1,000-4,000 ppm. SO_2 dissolved in water forms sulfurous acid:




[0035] Sulfurous acid is unstable, it exists only in aqueous solutions and as the temperature increase the equilibrium of reaction (10) shifts to the left and SO_2 is released. The solubility of SO_2 in water is 9.61% at 20°C and decreases with temperature. At 80°C its solubility is only 2.98%.


[0036] In the presence of oxidants, sulfurous acid oxidized gradually to sulfuric acid. In the presence of ozone the SO_2 dissolved according to the following:



and the dithionic acid is decomposed according to:




5 [0037] In the presence of NO_x in water:



10 [0038] And the formed NO is oxidized again to NO_2 and reaction (13) is repeated. Thus, NO acts as a catalyst, accelerating the oxidation of SO_2 .

[0039] In the presence of sulfoxides, SO_2 forms a complex with the sulfoxide group. (Neftechimija vol. 18, No. 2 p. 325-327). Infra-red studies show that a 1:1 complex of sulfoxide with SO_2 is formed through coordination bond of the oxygen of the SO group with the free electron pair on the sulfur atom of the sulfur dioxide.



20

25

[0040] Thus, using sulfoxides, simplifies and enhances the removing of sulfur dioxide from waste gases. Our studies show that in the presence of oil sulfoxide and water, SO_2 absorption is enhanced and the decomposition of H_2SO_3 to release SO_2 according to reaction 10 does not occur.

EXAMPLES

30 [0041] The following experiments demonstrate and clarify the present invention and do not intend to limit the scope of the invention by any way.

Example 1

35 [0042] A glass column of 400 mm height and 30 mm diameter was heated by an outer electric heater to 80°C . The glass column was filled with glass rings of 4mm height and 4 mm diameter and with 100 g emulsion of water in diesel derived sulfoxides comprising of 30 g water in 70 g sulfoxides.

[0043] A stream of air containing 1.9% (mass percent) NO_2 was bubbled continuously through the bottom of the column at a rate of 0.29 l/min for 42 hours continuously. About 75-90% of NO_2 was consumed.

40 [0044] After 42 hours, the liquid in the column was collected and separated into two phases. The concentration of nitric acid in the aqueous phase was 20.3 wt. %.

[0045] The amount of nitrous and nitric acid in the sulfoxide phase was determined by potentiometric titration in non-water medium and was found to be 21% of the total acid. In order to destroy the nitrous acid - sulfoxide complex, water were added to the organic phase and oxygen was bubbled into the liquid in order to oxidize all nitrous acid molecules, converting them into nitric ions which pass to the aqueous phase.

45 [0046] The sulfoxide phase obtained after the phase separation was combined with a fresh amount of water and reused as a scrubbing agent. After a large number of recycling the scrubbing agent by this procedure, no reduction in its absorption power was observed.

[0047] This experiment demonstrates that at concentration of more than 20% of nitric acid in the aqueous component of the emulsion, the scrubbing agent of the present invention still has capability of absorbing more pollutants.

50

Example 2

55 [0048] SO_2 absorption was conducted under the same conditions as in Experiment 1. SO_2 concentration in the input gas was 2000 ppm. The process was carried out for 42 hours during which more than 90% of SO_2 were absorbed without observing loss of absorption capability. The aqueous phase obtained at the end of the process contained only sulfuric acid. No sulfite ions (SO_3^-) were detected.

Example 3

[0049] NO₂ and SO₂ absorption was conducted simultaneously with the same reactor and emulsion composition as in Example 1 but at temperature of 20-25°C.

[0050] The concentration of NO₂ was 1000 ppm and that of SO₂ 800 ppm. The process was carried out for 8 hours continuously and during this time no reduction in the absorption capability of the scrubbing agent was observed. The average concentrations of NO₂ and SO₂ at the output were less < 10 ppm and < 2 ppm respectively.

[0051] The aqueous phase obtained after collecting and separating the emulsion contained a mixture of nitric and sulfuric acids.

Example 4

[0052] A stream of 1% NO diluted in N₂ (0.188 l/min) was combined with a stream of pure nitrogen (1.69 l/min) and a stream of ozonated air (2.2 l/min) and the gas mixture was passed through a two-section column reactor of 0.04 m diameter. Each section has a perforated disk on which a packed glass rings of 6 mm diameter and 6 mm height were placed. The height of the packed glass rings in each section was 0.38 m.

[0053] The gas mixture was passed upward through the bottom of the reactor and the scrubbing agent, oil-derived sulfoxide:water = 70:30 (weight ratio) was supplied dropwise into the column from its upper opening obtaining complete and uniform wetting of the glass rings by the liquid. The scrubbing agent was circulated through the reactor

[0054] The residence time of the gas in the reactor was 12 s.

[0055] The process was carried out for 29 hours.

[0056] The ozone was supplied into the reactor at a rate of 0.2 g/h, providing 40% of the molar amount required for complete oxidation of NO into NO₂. The oxidation took place in the reactor simultaneously with the absorption of NO₂ by the scrubbing agent.

[0057] The concentrations of NO and of NO₂ were measured by an automatic analyzer at the input and at the output of the reactor.

[0058] The average input concentrations were: 600 ppm NO and 20 ppm NO₂

The average output concentrations were: 7.2 ppm NO and 1 ppm NO₂

[0059] The average absorption of NO was 88% and of NO₂ 95%.

[0060] The calculated amount of NO passing through the reactor during 29 hours is 4.38 g (0.113 l/h × 29 h = 3.277 l = (30 g/mole × 3.277 l)/(22.4 l/mole)). Since only 88% of NO was absorbed, the calculated amount of HNO₃ that should have been formed in the aqueous phase is 7.6 g. The experimental result was 7.42 g, i.e., 97.6% yield.

Example 5

[0061] The removal of NO from the waste gas produced in a nitric acid production process was carried out in a glass reactor of 9.09 cm diameter. The reactor of 1 m height had a perforated plate at its bottom on which a packing of 9 mm diameter and 9 mm height glass rings had been placed. The packing layer volume was equal to 0.023 m³.

[0062] The waste gas from the chemical process was supplied to the reactor at a rate of 9.7 l/min. Ozonated air was supplied to the reactor at a rate of 5 l/min by an ozonator with an output of 0.15g ozone per hour, providing 40.5% of the stoichiometric amount required for full oxidation of NO into NO₂.

[0063] The absorbent (oil sulfoxide : water = 70 :30) was dosed into the reactor from its upper opening at a rate of 1530 ml/h.

[0064] The residence time of the gas inside the reactor was 9.4s.

[0065] The concentrations of NO and of NO₂, measured by an automatic analyzer at the input and at the output of the reactor were as follows:

average input concentrations: NO = 300 ppm, NO₂ = 50 ppm

average output concentrations: NO = 40 ppm, NO₂ = 2 ppm

NO absorption 87%, NOT absorption 96%.

[0066] Under the same conditions, but without ozone supply, 187 ppm of NO and 4 ppm of NO₂ were detected at the output, i.e., the NO absorption was 37.7% and the NO₂ absorption was 92%.

Example 6

[0067] In order to receive a complex fertilizing - ammonium nitrate and ammonium sulfate mixture, the aqueous phase received after one of the tests was separated from the organic phase (oil sulfoxides) and neutralized by aqueous solution of ammonium according to the following procedure:

10.2 g of NH_4OH solution with 13% NH_3 concentration were added on agitation to 30.0 g aqueous phase which contained 6.0% of HNO_3 and 6.0 g of H_2SO_4 . After neutralization, the pH of the solution was equal to 6.5. The obtained solution was boiled at 100 °C and the obtained mixture was dried out at 150°C degrees, obtaining 4.46 g of salts mixture. The analysis of the salts mixture gave the following composition:

2.1 g of NH_4NO_3 (92% of theoretical yield) and 2.36g of $(\text{NH}_4)_2\text{SO}_4$ (97.5% of theoretical yield).

Claims

1. A method for simultaneously removing acidic gases of sulfur and nitrogen oxides from waste gas before it is emitted to the atmosphere by contacting said waste gas with a scrubbing agent comprising an emulsion of water in organic sulfoxides in the presence of a stream of air or of ozonated air.
2. A method according to claim 1 wherein the waste gas is a combustion flue gas.
3. A method according to claim 1 wherein the waste gas is a gas mixture released from a chemical process.
4. A method according to claim 1 wherein the organic sulfoxides are oil derived sulfoxides.
5. A method according to claim 4 wherein the oil derived sulfoxides are derived from the diesel fraction of oil.
6. A method according to claim 1 wherein the weight ratio of water: organic sulfoxide in the emulsion is in the range 10:90 to 90: 10, preferably in the range 10:90 to 50:50.
7. A method according to claim 1 wherein the scrubbing agent is regenerated after it is loaded, by letting said scrubbing agent to separate into two phases, collecting the upper sulfoxide phase and adding to said sulfoxide phase a fresh amount of aqueous solution.
8. A method according to claim 7 wherein the aqueous phase obtained after the separation of phases contains nitric and/or sulfuric acids and is collected to be used as useful acid solutions.
9. A method according to claim 8 wherein ammonium salts are added to the acid solution obtained after the separation of phases to obtain a solution of ammonium nitrate and/or ammonium sulfate useful as a fertilizer.
10. A method for cleaning fuel gas from acid gases according to claim 1 wherein the aqueous phase of the emulsion further contains ammonium ions and wherein the solution of ammonium nitrate and/or ammonium sulfate obtained after separation of the emulsion is collected to be used as a fertilizing solution.
11. A method according to claim 9 or 10 wherein the source for the ammonium ions is selected from the group consisting of ammonia, ammonium carbonates and ammonium carbamate.
12. A method according to claim 1 wherein contacting the waste gas with said scrubbing agent is conducted in a tower embedded with inert particles and wherein the waste gas is passed upward through the tower and the emulsion is circulated downward in a rate which ensures complete wetting of inert particles.
13. A method according to claim 1 wherein contacting the waste gas with said scrubbing agent is conducted in a tower through which the waste gas is passed in an upward direction and the emulsion is sprayed into the tower from the upper opening of the tower forming a fog of said emulsion inside the tower.

Patentansprüche

1. Verfahren zum gleichzeitigen Entfernen von sauren Schwefel- und Stickstoffoxidgasen aus Abgas, bevor dieses an die Atmosphäre abgegeben wird, indem das Abgas mit einem Gaswaschmittel, das eine Emulsion von Wasser in organischen Sulfoxiden umfasst, in Gegenwart eines Luftstroms oder eines ozonisiertem Luftstroms kontaktiert wird.
2. Verfahren gemäß Anspruch 1, wobei das Abgas ein Verbrennungsabgas ist.

3. Verfahren gemäß Anspruch 1, wobei das Abgas eine Gas Mischung ist, die bei einem chemischen Verfahren frei wird.
4. Verfahren gemäß Anspruch 1, wobei die organischen Sulfoxide von Öl abgeleitete Sulfoxide sind.
5. Verfahren gemäß Anspruch 4, wobei die öl abgeleiteten Sulfoxide aus der Dieselölfraktion stammen.
6. Verfahren gemäß Anspruch 1, wobei das Gewichtsverhältnis von Wasser:organischem Sulfoxid in der Emulsion im Bereich von 10:90 bis 90:10, vorzugsweise in dem Bereich 10:90 bis 50:50 liegt.
7. Verfahren gemäß Anspruch 1, wobei das Gaswaschmittel, nachdem es beladen worden ist, regeneriert wird, indem das Gaswaschmittel in zwei Phasen aufgetrennt wird, die obere Sulfoxidphase gesammelt wird und zu dieser Sulfoxidphase eine frische Menge einer wässrigen Lösung hinzugegeben wird.
8. Verfahren gemäß Anspruch 7, wobei die wässrige Phase, die nach der Phasentrennung erhalten wird, Salpeter- und/oder Schwefelsäuren enthält und gesammelt wird, um als geeignete saure Lösungen verwendet zu werden.
9. Verfahren gemäß Anspruch 8, wobei zu der sauren Lösung, die nach der Phasentrennung erhalten wird, Ammoniumsalze zugegeben werden, um eine Lösung von Ammoniumnitrat und/oder Ammoniumsulfat, die als Düngemittel geeignet sind, zu erhalten.
10. Verfahren zum Reinigen von Verbrennungsabgasen von sauren Gasen gemäß Anspruch 1, wobei die wässrige Phase der Emulsion ferner Ammoniumionen enthält und wobei die Ammoniumnitrat- und/oder Ammoniumsulfatlösung, die nach der Abtrennung der Emulsion erhalten wird, gesammelt wird, um als eine Düngemittellösung verwendet zu werden.
11. Verfahren gemäß Anspruch 9 oder 10, wobei die Quelle für die Ammoniumionen ausgewählt ist aus der Gruppe, die besteht aus Ammoniak, Ammoniumcarbonaten und Ammoniumcarbamat.
12. Verfahren gemäß Anspruch 1, wobei das Kontaktieren des Abgases mit dem Gaswaschmittel in einem Turm durchgeführt wird, in dem Inertpartikel eingebettet sind, und wobei das Abgas von unten nach oben durch den Turm geleitet wird und die Emulsion nach unten in einer Geschwindigkeit zirkuliert wird, die das komplette Benetzen der Inertpartikel ermöglicht.
13. Verfahren gemäß Anspruch 1, wobei das Kontaktieren des Abgases mit dem Gaswaschmittel in einem Turm durchgeführt wird, durch den das Abgas von unten nach oben geleitet wird und die Emulsion von der oberen Öffnung des Turms in den Turm gesprüht wird, wobei in dem Turm ein Nebel aus der Emulsion gebildet wird.

Revendications

1. Procédé pour l'élimination simultanée de gaz acides de soufre et d'oxydes d'azote à partir de gaz résiduels avant leur émission dans l'atmosphère par mise en contact desdits gaz résiduels avec un agent de nettoyage comprenant une émulsion d'eau dans des sulfoxydes organiques en présence d'un courant d'air ou d'air ozonisé.
2. Procédé selon la revendication 1, dans lequel le gaz résiduel est un gaz de combustion.
3. Procédé selon la revendication 1, dans lequel le gaz résiduel est un mélange de gaz émanant d'un processus chimique.
4. Procédé selon la revendication 1, dans lequel les sulfoxydes organiques sont des sulfoxydes dérivés du pétrole.
5. Procédé selon la revendication 4, dans lequel les sulfoxydes dérivés du pétrole sont dérivés de la partie diesel du pétrole.
6. Procédé selon la revendication 1, dans lequel le rapport de poids eau/sulfoxyde organique dans l'émulsion est de l'ordre de 10/90 à 90/10, de préférence de l'ordre de 10/90 à 50/50.

7. Procédé selon la revendication 1, dans lequel l'agent de nettoyage est régénéré après avoir été chargé, en laissant ledit agent de nettoyage se séparer en deux phases, en récoltant la phase sulfoxyde supérieure et en ajoutant à ladite phase sulfoxyde une nouvelle quantité de solution aqueuse.
- 5 8. Procédé selon la revendication 7, dans lequel la phase aqueuse obtenue après la séparation de phases contient des acides nitriques et/ou sulfuriques et est récoltée pour être utilisée comme solution acide utile.
9. Procédé selon la revendication 8, dans lequel des sels d'ammonium sont ajoutés à la solution acide obtenue après la séparation de phases pour obtenir une solution de nitrate d'ammonium et/ou de sulfate d'ammonium utile comme fertilisant.
- 10 10. Procédé pour nettoyer le gaz combustible de ses gaz acides selon la revendication 1, dans lequel la phase aqueuse de l'émulsion contient en outre des ions d'ammonium et dans lequel la solution de nitrate d'ammonium et/ou de sulfate d'ammonium obtenue après la séparation de l'émulsion est récoltée pour être utilisée comme une solution fertilisante.
- 15 11. Procédé selon la revendication 9 ou 10, dans lequel la source d'ions d'ammonium est choisie à partir du groupe composé d'ammoniac, de carbonates d'ammonium et de carbamate d'ammonium.
- 20 12. Procédé selon la revendication 1, dans lequel la mise en contact du gaz résiduaire avec ledit agent de nettoyage est effectuée dans une tour contenant des particules inertes et dans lequel le gaz résiduaire est envoyé vers le haut par la tour et on fait circuler l'émulsion vers le bas à une vitesse qui assure l'humidification complète des particules inertes.
- 25 13. Procédé selon la revendication 1, dans lequel la mise en contact du gaz résiduaire avec ledit agent de nettoyage est effectuée dans une tour dans laquelle le gaz résiduaire est envoyé vers le haut et l'émulsion est pulvérisée dans la tour par l'ouverture supérieure de la tour, formant une buée de ladite émulsion à l'intérieur de la tour.

30

35

40

45

50

55